

12,1" TFT replacement monitors for

- ✓ 14" CRT colour monitor
- ✓ FANUC Serien 0-MC, 0-TC, 0-MD, 6M, 6T, 10T, 10M, 11M, 11T,
- ✓ FANUC Serien 15A, 15B, 15M, 15T, 16, 16T, 16M, 18, 18M, 20, 20T

Item-No.: **LCD12-0002**

Our TFT industrial monitors are designed specifically for the replacement of CRT monitors manufactured in many different controls.

Conversion works quick and easy with plug & play.



Technical specifications

Display	12,1" TFT Full Colour active, 800 x 600 pixels
Replacement monitor for CRT	A61L-0001-0074, A61L-0001-0094, A61L-0001-0096, A02B-0222-C071, A02B-0163-C322, DNC96, Toshiba D14CM-01A, Hitachi C14X-1472DF, Matsushita TX-1450ABA, Tatung CD14JBS
Active area TFT screen	249 x 188 mm (w x h)
Frequency	15 - 45 kHz horizontal, 50 - 75 Hz vertical
Connector	20pin HONDA connector male / 20pin male, silver / 20pin female, silver
Housing dimension	323 x 220 mm (w x h)
Settings	via OSD (On Screen Display)
Power supply	AC 85-240V
Temperature range	-10° to 55°C operating temperature
Manufactured according to	CE industry standard, EN55022, EN55024

Note: Subject to change without notice, errors excepted 07.2013

